



BCS-01

1D Wired Laser Barcode Scanner



2. Technical parameters

Product Specification:BCS-01 1D Wired Laser Barcode Scanner	
Technical parameter	
Light source	650 (visible laser)
Scan model	single line Bi-directional
Scan speed	300 scans/sec
Resolution	4mil
Width of scan	5-30cm
Depth of scan	2-50cm
Scan angles	Roll30°、Pitch75°、Yaw65°
Decode capacity	Code39、Code 39Full ASCII、Code128Full 、ASCII、Codabar、Interleaved 2 of 5、Code93、MSI、Code11、ISBN、ISSN、china post code、UPC/EAN、UPC/EAN(include complement code)、Code128、UCC/EAN128、etc
Interface	USB
Print contrast	30% minimum
Bit error rate	1/5 million
Prompt	Buzzer, Indicator light
Scan model	Handheld / Continuous scanning
Weight	0.25kg
Material	ABS+PC
Cable standard	Straight: 1.8m
Electrical parameter	
Power supply	DC 5V $\pm$ 5%
Current	Working: 50mA Standby: 30mA
Laser security	Accord with national level1 laser security standards
Environment parameter	
Temperature	Working: 0℃-50℃ / 32°to 122°F Storage :0℃-50℃ / 32°to 122°F
Humidity	Operating and Storage humidity 20%-85% (non-condensing)
ESD protection	15KV air discharge
Anti-knock	1.5m free fall on concrete surface
Certificate:	CE, FCC, RoHS , IP54