



BCS-03

2D Wired Barcode Scanner



2. Technical parameters

Product Specification: BCS-03 2D Wired Barcode Scanner		
Scanner parameters:		
CPU: ARM 32-bit Cortex		Sensor: CMOS 640*480
Resolution : 4mil		Light aimer: 624nm LED
Printing Contract : ≥25%		Material: ABS+PC
Indication: Buzzer & LED		Interface : USB
Decoding speed: 500scans/sec		Anti inference: 0-100000Lux Max
Button life : 5000,000 times		Voltage:5V DC
Depth of Field	13mil-EAN13	40-250mm
	4mil-code39	50-90mm
	20mil-QR	40-290mm
	10mil-PDF417	40-260mm
Decode Capability: 1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, RSS, Codabar, ISBN、ISSN、GS1 DataBar(RSS14)etc. 2D: QR Code、Micro QR、Data Matrix、PDF417 etc.		
Trigger Mode: Handheld,Continuous, Auto-Induction		
Scanning angle: Angle of rotation360°, inclination± 65°,declination ± 60°		
Current: 80mA(working current), 30mA(standby current)		
Temperature: -20℃-50℃(Working) -40℃-60℃(Storage)		
Drop test : 1.5m		
Operating Humidity: 5 - 95% (non-condensing)		
Certificate : CE, FCC, RoHS, IP54		

3. Packaging Details

- * Standard List: Scanner *1, USB Cable *1, Manual *1, Box *1.
- * Single Package Size: 200*70*100mm
- * Single Gross Weight: 0.25kg
- * 50pcs/CTN Carton Size: 535*420*350mm
- * 50pcs/CTN Carton G.W.:13Kg, N.W:11Kg