



BCS-04

2D Desktop Barcode Scanner



2. Technical parameters

Product Specification: BCS-04 2D Desktop Barcode Scanner	
Scanner parameters:	
Optical resolution	CMOS 640 pixels (H) x 480 pixels (V)
Lighting source	red LED supplement
Resolution	≥4mil
Scanning speed	1500 times/s
Scanning angle	Roll 360° / Pitch ±55° / Yaw ±55°
Sweeping barcode type	paper, thin film medium one-dimensional; mobile phone, flat screen, etc.
Printing contrast	20%
Error rate	≤1/2,000,000
Interface type	USB
Prompt mode	Buzzer, LED
Decoding Capability	1D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA、Matrix 2 of 5、Code 11、Code 128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.
	2D: PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec
Electric voltage	5V DC
Current	Work Current 200mA, Stand-by Current 110mA, Starting Current 280mA
Ambient Light Immunity	0-100,000 Lux
Mechanical parameters	
Dimensions	155mm x 100mm x100mm
Weight	200g
Enviromental parameter	
Working temperature	-20℃～60℃
Storage temperature	-30℃～70℃
Humidity	5% to 95% relative humidity, non-condensing
Drop test	2m

3. Packaging Details

- * Standard List: Desktop Scanner*1, Cable *1, Manual *1, Box *1.
- * Single Package Size: 170*135*105mm
- * Single Gross Weight: 0.45kg
- * 30pcs/CTN Carton Size: 545*420*360mm
- * 30pcs/CTN Carton G.W.:15Kg, N.W:13.5Kg